

## DESCRIPTION

Three-Dimensional Model Processing Apparatus, Three-Dimensional Model Processing Method and Program Providing Medium

## Technical Field

This invention relates to a three-dimensional model processing apparatus, a three-dimensional model processing method and a program providing medium for implementing processing such as deformation, coloring etc. to three-dimensional model displayed on display of personal computer, etc., and more particularly to a three-dimensional model processing apparatus, a three-dimensional model processing method and a program providing medium which can change various attributes such as shape or color, etc. of three-dimensional model displayed on display in accordance with operation of operator to display it as the result of the fact that operator operates object tool as virtual object corresponding to three-dimensional model displayed on display and various editing tools such as a shape change tool, a coloring tool, etc.

## Background Art

In the field of computer graphics, there have been developed and realized various techniques with respect to apparatuses or methods for displaying three-dimensional graphic on display to execute change processing of orientation or shape,

etc. of displayed three-dimensional graphic. As display technique onto display of three-dimensional object, there is a method of inputting shape data of object including depth data by using, e.g., a mouse or a two-dimensional tablet, etc. Further, there is also used a method of acquiring data of actual three-dimensional objects by a three-dimensional digitizer or a three-dimensional scanner to acquire display data on the basis of that data to display such display data on display. In addition, as a method of carrying out processing such as deformation, etc. of object displayed on display, there is known a configuration using input unit comprised of manipulator of the glove type.

An example of the configuration of a shape change processing apparatus of display object using the manipulator of the glove type is shown in FIG. 1. In FIG. 1, operator fits or attaches a head mount display 10 to observe an object 30 on display. Further, a manipulator 11 of the glove type is fitted or attached at hand of operator.

Pressure sensor or magnetic sensor for detecting movement of hand and finger is attached at the manipulator 11, and movement of hand of operator is detected. A detection signal is inputted to a control unit 20 through an I/O 22. A CPU 21 executes processing in accordance with program stored in a ROM 24 or a RAM 25, and executes change processing, etc. of display parameter relating to the display object 30 in accordance with the detection signal to generate new three-dimensional shape data to display, on the head mount display 10, three-dimensional object 30 based on new display parameter through display control means 23.

For example, in the case where operator executes operation to shave the side

surface of the three-dimensional object 30 on display by using the manipulator 11 of the glove type, sensor of the manipulator 11 detects shaving operation of the manipulator 11, and the CPU 21 changes display parameter of the displayed object 30 on the basis of detection signal inputted through the I/O 22 to display, on the head mount display 10, displayed object in which shaved portion 31 is formed.

As stated above, in conventional three-dimensional information input systems, various techniques are used. In the previously described processing system using mouses or two-dimensional tablets, since such processing is input processing by two-dimensional information, there exist restriction and/or feeling of disagreement with respect to operation of the three-dimensional object. Further, various processing such as movement, deformation, cutting, etc. with respect to displayed object must be carried out by using only a single editing tool, e.g., mouse, resulting in the problem that operator is difficult to intuitively grasp setting of the editing tool.

Inputs by three-dimensional digitizer and/or three-dimensional scanner are useful for input of shape of virtual objects, but are not suitable for deformation processing, etc. of inputted objects. Such input units are expensive.

Input processing by the manipulator of the glove type is input processing which can be intuitively processed by the operator. However, in practice, any initial setting processing is required before actual processing, e.g., carrying out "push" operation with respect to the object, or carrying out "pull" operation with respect thereto, and there is therefore the drawback that handling is difficult for a user who is unfamiliar

with the units. These input units are also considerably expensive.

#### Disclosure of the Invention

This invention has been made in view of the problems of the above-described prior art, and its object is to provide a three-dimensional model processing apparatus, a three-dimensional model processing method and a program providing medium in which operator operates respective tools in a form closer to more practical processing by using virtual objects and various tools corresponding to respective processing, thereby making it possible to execute various processing of objects such as shape change, surface coloring, etc. with respect to the three-dimensional by displayed objects.

This invention has been made in view of the above-mentioned task, and includes a display unit for three-dimensionally displayed objects to be edited, an object tool in which movement and orientation change can be made, an editing tool in which relative distance with respect to the object tool can be changed, and processing means for detecting relative position between the object tool and the editing tool to execute processing set in correspondence with the editing tool on the basis of the detected relative positional information to change attribute information of the object to be edited displayed on the display unit.

In this invention, the processing means further includes configuration for detecting position information of the changed object tool based on movement and

orientation change of the object tool to change attribute information of the object to be edited displayed on the display unit on the basis of the detected position information.

Further, the processing means includes configuration which can execute plural different processing corresponding to the kind of editing tools.

Further, the processing means includes configuration which executes processing set in correspondence with editing tool on the basis of relative position information including at least one of relative distance between the object tool and the editing tool and relative angle between the object tool and the editing tool.

Further, attribute information of objects to be edited that the processing means changes is either one of attribute information relating to shape, color and sound of the object to be edited displayed on the display unit.

Further, the processing means includes configuration for executing functional operation of the object to be edited displayed on the display unit as processing set in correspondence with the editing tool.

Further, this invention is directed to a three-dimensional model processing method for executing various processing with respect to the object to be edited three-dimensionally displayed on a display unit, and this method includes a step of detecting relative position between object tool in which movement and orientation change can be made and editing tool in which relative distance with respect to the object tool can be changed, and a step of executing processing set in correspondence with the editing

tool on the basis of the detected relative position information to change attribute information of the object to be edited on display.

This invention further includes a step of detecting position information of the changed object tool based on movement and orientation change of the object tool, and a step of changing attribute information of the object to be edited displayed on the display unit on the basis of the detected position information.

This invention further includes a step of discriminating a kind of the editing tool, and serves to execute processing corresponding to the kind of the discriminated editing tool.

Further, at the step of detecting relative position, relative position including at least either one of relative distance between the object tool and the editing tool and relative angle between object tool and editing tool.

Further, attribute information is either one of attribute information relating to shape, color and sound of object to be edited displayed on display means.

In this invention, functional operation of the object to be edited displayed on the display unit is executed as processing set in correspondence with the editing tool.

In addition, this invention is directed to a program providing medium for providing computer program for executing, on computer system, three-dimensional model processing which executes various processing with respect to the object to be edited three-dimensionally displayed on a display unit, wherein the computer program recorded with respect to this recording medium includes a step of detecting relative

position between object tool in which movement and orientation change can be made and the editing tool in which relative distance with respect to the object tool can be changed, and a step of executing processing set in correspondence with the editing tool on the basis of the detected relative position information to change attribute information of the object to be edited displayed on display means.

The program providing medium adapted so that computer program is recorded is medium for providing, in a form such that computer can read, computer program with respect to, e.g., widely used computer system which can execute various program codes. As the medium, there are recording medium such as CD, FD or MO, etc., and transmission medium such as network, etc. and their forms are not particularly limited.

Such program providing medium defines cooperative relationship in structure or function between the computer program and the providing medium for realizing function of a predetermined computer program on computer system. In other words, by installing computer program into the computer system through the providing medium, the cooperative action is exhibited in the computer system.

Still further objects of this invention and more practical merits obtained by this invention will become more apparent from the description of embodiments which will be given below.

#### Brief Description of the Drawings

FIG. 1 is a block diagram for explaining conventional three-dimensional model

processing configuration using glove type manipulator.

FIG. 2 is a block diagram showing the configuration of a three-dimensional model processing apparatus according to this invention.

FIG. 3 is a view for explaining outline of processing in the three-dimensional model processing apparatus according to this invention.

FIG. 4 is a view showing an example of the configuration in which a tablet is used in input unit in the three-dimensional model processing apparatus according to this invention.

FIG. 5 is a view showing an example of the configuration in which magnetic sensors are used in input unit in the three-dimensional model processing apparatus according to this invention.

FIG. 6 is a view showing an example of the configuration in which ultrasonic sensors are used in input unit in the three-dimensional model processing apparatus according to this invention.

FIG. 7 is a view showing an example of the configuration in which ultrasonic transponders are used in input unit in the three-dimensional model processing apparatus according to this invention.

FIG. 8 is a view showing, as flowchart, processing in the three-dimensional model processing apparatus according to this invention.

FIG. 9 is a view showing, as flowchart, processing in the case where a trowel is used as the editing tool in the three-dimensional model processing apparatus according



to this invention.

FIG. 10 is a view showing, as data flow diagram, processing in the case where a trowel is used as the editing tool in the three-dimensional model processing apparatus according to this invention.

FIG. 11 is a view showing, as flowchart, processing in the case where a pinch is used as the editing tool in the three-dimensional model processing apparatus according to this invention.

FIG. 12 is a view showing, as data flow diagram, processing in the case where a pinch is used as the editing tool in the three-dimensional model processing apparatus according to this invention.

FIG. 13 is a view showing, as flowchart, processing in the case where a brush is used as the editing tool in the three-dimensional model processing apparatus according to this invention.

FIG. 14 is a view showing, as data flow diagram, processing in the case where a brush is used as the editing tool in the three-dimensional model processing apparatus according to this invention.

FIG. 15 is a view showing, as flowchart, processing in the case where a spray is used as the editing tool in the three-dimensional model processing apparatus according to this invention.

FIG. 16 is a view showing, as data flow diagram, processing in the case where a spray is used as the editing tool in the three-dimensional model processing apparatus

according to this invention.

FIG. 17A shows action area in the case where a spray is used as the editing tool in the three-dimensional model processing apparatus according to this invention, and FIG. 17B is a view showing coloring range in the case where spray is used as editing tool.

FIGS. 18A, 18B and 18C are views for explaining more practical examples of the configuration using the three-dimensional model processing apparatus according to this invention.

FIG. 19 is a view for explaining a more practical example of the configuration using the three-dimensional model processing apparatus according to this invention.

#### Best Mode for Carrying Out the Invention

This invention will now be described with reference to the attached drawings.

FIG. 2 shows a block diagram showing an embodiment of a three-dimensional model processing apparatus according to this invention. The three-dimensional model processing apparatus 100 of this embodiment includes central processing unit (CPU) 101 for executing processing program, program memory 102 into which processing program is stored, data memory 103 in which processing data and information such as attribute of position, orientation, shape, color, etc. of the object to be edited or attribute of editing tool, etc. are stored, frame memory 104 in which picture information for displaying, on picture display unit 110, object to be edited, editing tool and instruction

to user, etc. are stored, input unit 105 for inputting various instructions with respect to the object to be edited, external storage unit 106 for storing observation information or processing result, and bus 107 for permitting data transfer between these respective units. The picture display unit 110 is connected through the frame memory 104. Thus, picture data stored in the frame memory 104 is displayed. The input unit 105 which is characterized means in this invention is constituted by plural groups of tools for carrying out various processing such as deformation, surface color change, etc. with respect to the object to be edited having three-dimensional shape displayed on the picture display unit 110.

Prior to more practical description of respective means of FIG. 2, the concept of this invention will be described with reference to FIG. 3. The three-dimensional model processing apparatus of this invention includes, as shown in FIG. 3, object tool 301 corresponding to the object to be edited and editing tools 302 to 306 for implementing various processing to the object to be edited, which are displayed on display. By using these tools, processing such as deformation, coloring, etc. with respect to object 308 to be edited displayed on display 307 is executed.

In FIG. 3, as editing tools, there are shown push tool 302 having, e.g., shape of "trowel" for executing "push" operation with respect to the object to be edited, pull tool 303 having shape of pinch for executing "pull" operation with respect to the object to be edited, brush tool 304 having, e.g., shape of "brush" for executing "fine coloring" operation with respect to the object to be edited, spray tool 305 having, e.g., shape of

“color spray” for executing “rough coloring” operation with respect to the object to be edited, and cut tool 306 having, e.g., shape of “knife” for executing “cut off, separate” operation with respect to the object to be edited.

As the result of the fact that operator operates various tools shown in FIG. 3 in a predetermined action area (sensor detection area) as indicated by 201 to 204 in FIG. 3, in more practical sense, carries out change of distance between object tool 301 and editing tools 302 to 306 and change of angle therebetween, processing corresponding to respective tools, i.e., deformation of the object to be edited corresponding to “push” operation by push tool 302 and “pull” operation by pull tool 303, and/or change of surface color of the object to be edited corresponding to brush tool 304 and spray tool 305 are implemented to object 308 to be edited displayed on display 307.

As metaphor of clay model subject to operation such as deformation or coloring, etc., input information from sensor for detecting position and orientation in the three-dimensional space is used. This is clay object sensor, and tool 301 for object of FIG. 3. The object tool may be three-dimensional shape as shown in FIG. 3, spherical shape or shape approximate to the object to be edited displayed on display. This object tool 301 has the configuration that operator can hold it by one hand so that it can be freely moved or rotated.

Moreover, editing tool metaphor for carrying out deformation or coloring with respect to the object to be edited also has, as parameter, input information from sensor for detecting position and orientation in the three-dimensional space. The editing tool

has shape that operators can intuitively associate processing mode in accordance with respective processing. Namely, as shown in FIG. 3, there are shape of "trowel" as push tool 302. shape of "pinch" as pull tool 303, shape of "brush" as brush tool 304, shape of "spray" as spray tool 305 and shape of "knife" as cut tool 306, etc.

These object tool 301 and editing tools 302 to 306 correspond to the input unit 105 in FIG. 2, and more practical example of the configuration of this input unit will be described with reference to FIGS. 4 to 7. It is to be noted that, in FIGS. 4 to 7, the editing tools 302 to 306 are described in the state roughly divided into tool for deformation and tool for color without finely classifying them.

FIG. 4 is an example where input unit is constituted with tablet 404. Position information and orientation information of object tool 401, deformation tool 402 and coloring tool 403 are detected by input through input tablet 404, and detection data are inputted. Detection function by chip or coil is added to the object tool 401, the deformation tool 402 and the coloring tool 403 similarly to input pen associated with conventional tablet, and position and orientation information of respective tools are detected. When coils from which detection values different from each other are obtained are provided on respective surfaces 1 to 6 of object tool 301 of hexahedron as shown in FIG. 3, for example, mounting surfaces on the tablet are discriminated, thus making it possible to obtain three-dimensional information from these mounting surfaces. Alternatively, there may be employed a configuration in which Z-axis information obtained from other optical sensor or magnetic sensor is combined with

XY axis two-dimensional information obtained from tablet to thereby discriminate three-dimensional position to obtain three-dimensional data.

FIG. 5 is an example where input unit is constituted by using magnetic sensors. The area within magnetic field produced from magnetic source 504 is caused to be action area, and operations by object tool 501, deformation tool 502 and coloring tool 503 are carried out within the action area. Magnetic sensors are respectively attached to the object tool 501, the deformation tool 502 and the coloring tool 503, and the magnetic sensors of the object tool 501, the deformation tool 502 and the coloring tool 503 output magnetic displacement data to dedicated interface hardware 505 within the action area set within magnetic field produced from the magnetic source 504. The dedicated interface hardware 505 calculates position information data, orientation information data of respective tools on the basis of these data. It is to be noted that the dedicated interface hardware 505 shown in FIG. 5 may be replaced by calculation processing program of software.

FIG. 6 is an example where the input unit is constituted by using ultrasonic sensors. The area where ultrasonic wave produced from a ultrasonic transmitting section 604 can be detected is caused to be action area, and processing operations by object tool 601, deformation tool 602 and coloring tool 603 are carried out within the action area. Ultrasonic sensors are respectively attached to the object tool 601, the deformation tool 602 and the coloring tool 603, and the ultrasonic sensors of the object tool 601, the deformation tool 602 and the coloring tool 603 within the action area

which is the area where ultrasonic wave produced from the ultrasonic transmitting section 604 can be detected detect arrival times from source of ultrasonic wave or interference of ultrasonic wave, etc. Dedicated interface hardware 605 calculates position information data and orientation information source data of respective tools on the basis of these data. It is to be noted that the dedicated interface hardware 605 shown in FIG. 6 may be replaced by calculation processing program of software.

FIG. 7 is a second example where the input unit is constituted by using ultrasonic sensor. A ultrasonic transmitting/receiving section 704 carries out transmitting and receiving of ultrasonic wave. The area where ultrasonic wave produced from the ultrasonic transmitting/receiving section 704 can be detected is caused to be action area, and processing operations by object tool 701, deformation tool 702 and coloring tool 703 are carried out within the action area. Transponders having a function to receive ultrasonic wave produced from the ultrasonic transmitting/receiving section 704 to send back it are respectively attached at the object tool 701, the deformation tool 702 and the coloring tool 703. The ultrasonic transmitting/receiving section 704 receives ultrasonic waves sent back from respective tools to detect time required for going and returning of ultrasonic wave or interference of ultrasonic wave, etc. to calculate position information data and orientation information source data of respective tools on the basis of these data.

The input unit 105 shown in FIG. 2 is realized as input device using various sensors as described above. It is to be noted that information input/output with respect

to three-dimensional model processing apparatus 100 from sensors of respective tools may be configuration through data line of wire or wireless data transmitting/receiving configuration. In addition, as the configuration of the input unit 105, there may be employed combination of the various sensors.

As the external storage unit 106 shown in FIG. 2, random accessible memory medium such as hard disk drive (HDD) or optical disk, etc. is desirable. In addition to the above, the external memory unit may be constituted by tape streamer or non-volatile semiconductor memory represented memory stick. In addition, it is also possible to utilize external storage unit of network-connected other system.

The central processing unit (CPU) 101 executes processing in accordance with processing program recorded in the program memory 102.

Flow of processing using the three-dimensional model processing apparatus shown in FIG. 2 will now be described in accordance with the processing flow of FIG. 8. The processing flow shown in FIG. 8 is processing executed in accordance with processing program recorded in the program memory 102.

In FIG. 8, the example of the case where push tool 302, pull tool 303, brush tool 304 as coloring tool and spray tool 305 which have been explained with reference to FIG. 3 are used as editing tool will be explained. In addition to the above, it is possible to use various editing tools for executing various processing.

Initially, at step S801 of FIG. 8, data of position and orientation, etc. on the three-dimensional space of the object to be edited are acquired. Such data are data



stored in the data memory 103 shown in FIG. 2 and corresponding to attribute data such as position, orientation, shape, color, etc. of the object to be edited displayed on the picture display unit 110. Initial position of the object tool 301 shown in FIG. 3 is set as position and orientation corresponding to these attribute data. Thereafter, in the case where operator moves object tool 301 within the action area which is the area where position detection by sensor can be made, the position and the orientation are detected by sensor output of the object tool 301, and attribute is rewritten in accordance with movement. Thus, the object to be edited is displayed on the picture display unit 110 on the basis of the rewritten attribute.

Then, at step S802, whether or not tool, i.e., object tool and editing tool such as deformation, and coloring, etc. are included within the action area is checked. The action area is each detectable area of various sensors used as the input unit. In the case where tablet is used as the input unit, the action area is tablet area. In the case where a magnetic sensor is used as the input unit, the action area is detectable area of the magnetic sensor. In the case where an ultrasonic sensor is used as the input unit, the action area is detectable area of the ultrasonic sensor.

When it is judged at step S803 that tool is not included within the action area, processing jumps to step S814. In the case where it is judged that tool is included within the action area, processing proceeds to step S804 to judge the kind (ID) of tool. The judgment of the tool kind here is judgment with respect to the kind of editing tool such as deformation, coloring, etc. With respect to the kind of these editing tools,

operator himself may designate the tool to input identification data (ID) indicating the tool kind, or may employ configuration for outputting identification signal (ID) from editing tool existing in the action area to carry out discrimination of the tool on the basis of identification signal.

When the kind of editing tool is judged at the step S804, processing proceeds to processing of steps S805 to S812. The processing from the step S805 to the step S806 is processing in the case where the editing tool is push tool, the processing from the step S807 to the step S808 is processing in the case where the editing tool is pull tool, the processing from the step S809 to the step S810 is processing in the case where the editing tool is brush tool, and the processing from the step S811 to the step S812 is processing in the case where the editing tool is spray tool. The respective processing of the steps S806, S808, S810, S812 are subroutines corresponding to respective tools, and are called at the time point when the editing tool is specified and are executed. In the case where the editing tool does not correspond to any tool, processing proceeds to step S813, at which warning is produced. Such warning is, e.g., processing for displaying warning message on the picture display unit 110 shown in FIG. 2, or outputting warning sound, etc.

Explanation will be given below with reference to FIG. 9 and figures succeeding thereto in connection with respective processing of the steps S806, S808, S810, S812, i.e., subroutine processing corresponding to respective editing tools.

At step S814, respective editing tools are displayed on the picture display unit

110, and display of the object to be edited processed by the editing tool is carried out. The display modes (form) of respective editing tools are modes based on shape data set every editing tool in advance. For example, if the editing tool is push tool, shape of "trowel" is displayed on the picture display unit 110. If the editing tool is spray tool, shape of "spray" is displayed on the picture display unit 110. Moreover, the object to be edited is displayed as object to which deformation or coloring is applied by each editing tool. Namely, objects to be edited in which attributes such as position, orientation, shape, color, etc. of the object to be edited changed by respective editing tools are reflected are displayed. Attributes of objects to be edited rewritten by operation by operator of respective editing tools are stored into the data memory 103 shown in FIG. 2.

Further, at step S815, completion of processing is judged. Completion of processing may be input from user who is operator, or rule prescribed within the processing application. For example, in the case of game program, completion of processing may be completion command by game over. In addition, judgment of completion based on restriction of hardware or software such as memory full, etc. may be carried out. In the case where it is judged at the step S815 that processing is not completed, processing returns to start of the processing flow to repeatedly execute similar processing.

The detail of the subroutine processing shown in FIG. 8 will now be described. FIG. 9 is a flow for explaining processing in the case where push tool is applied to the

object to be edited to apply deformation. Step S901 is step for obtaining position/orientation data on the three-dimensional space of "trowel" used as push tool. As previously described, such data are data obtained on the basis of respective sensor outputs in accordance with the kind of input unit utilized, i.e., tablets, magnetic sensors or ultrasonic sensors.

Then, step S902 is processing for determining space relationship/relative position between the object to be edited and the editing tool from position/orientation data of the object to be edited which has been acquired at the previously mentioned step S801 of FIG. 8 and position/orientation data of editing tool "trowel" determined at the step S901.

Then, at step S903, judgment as to whether or not deformation processing of the object to be edited using editing tool "trowel" is executed is carried out. In more practical sense, this judgment serves to carry out whether or not position data of editing tools detected by various sensors are admitted into the object to be edited. It is to be noted that it is not necessary that editing tools 302 to 306 are actually in the object tool 301 in FIG. 3 in this case, but there may be employed configuration to execute processing which determines that in the case where both tools are close so that the distance therebetween is less than a predetermined value, it is judged that the editing tool is admitted into the object to be edited.

Alternatively, object tool 301 may be constituted with, e.g., deformable sponge shaped material to also employ configuration such that editing tool can actually enter

the object tool 301. In this case, there may be employed a configuration to execute deformation of the object to be edited displayed on the picture display unit 110 on the basis of actual position data of the editing tool and the object tool in a manner caused to be in correspondence with the actual position data.

Deformation processing of the object to be edited displayed on the picture display unit 110 at step S904 can be realized by moving positions of vertices of polygons when display data is polygons data. In this case, in the case where distance between vertices is greatly apart, processing for generating new vertices is executed. Moreover, in the case where the object to be edited is represented as parametric curves, their control points are moved. Further, in the case where the object to be edited is represented by voxels, deformation can be realized by (Boolean operation) processing to add data. The deformation processing is carried out in accordance with data mode (form). In either case, processing based on displacement data of relative distance between object tool and editing tool is carried out.

After deformation processing of the object to be edited is executed at the step S904, rewritten attribute data of the object to be edited of deformed result is stored into the data memory 103 or external storage unit 106 shown in FIG. 2 at step S905.

In order to supplement explanation of the flowchart shown in FIG. 9, explanation will be further given in connection with processing in the case where push tool "trowel" is used with reference to the data flow diagram of FIG. 10. The data flow diagram is a view showing flow of data extending from data source within the object

to target within other object via process for converting data. The data flow diagram is constituted by processes (indicated as ellipses) for converting data, data flows (indicated as arrows) for carrying data, actor objects (indicated as rectangles) indicating production and consumption of data, and data store objects (indication put between two lines) for passively carrying out storage of data.

The data flow of FIG. 10 is processing by push tool "trowel", and processing is started by operation of the object tool (sensor) 1001 as an actor object and the trowel tool (sensor) 1002.

From the object tool 1001, orientation information and position information of the object are acquired. From the trowel tool 1002, position information of the tool is acquired.

Further, from shape information of the object which is attribute of the object to be edited which has been acquired in advance, surface attribute information of the object, orientation information and position information of object and position information of tool which are stored in the data memory 103 of FIG. 2, calculation processing 1003 of degree of deformation is executed. On the basis of this calculation, processing for changing attribute information, i.e., deformation processing 1004 is executed. In combination with these processing, rendering processing 105 as processing for generating display picture with respect to the picture display unit 110 is executed. Thus, rendering processing result is stored in the memory for display, i.e., the frame memory 104 of FIG. 2, and is displayed on the picture display unit 110.

FIG. 11 is a flow for explaining processing in the case where pull tool “pinch” is applied to the object to be edited to apply deformation. Step S1101 is step for obtaining position data and orientation data on the three-dimensional space of “pinch” used as pull tool. As previously described, such data are data obtained on the basis of respective sensor outputs in accordance with kind of input unit utilized, i.e., tablets, magnetic sensors and ultrasonic sensors.

Then, at step S1102, whether or not the switch of the pinch is pushed down is judged. The pull tool “pinch” of this embodiment has the configuration in which the switch is provided at the pull tool “pinch” for determining the start point and the end point of the pull operation to set the position at the time point when the switch is pushed down as the start point (“ON”) or the end point (“OFF”) of the pull operation with respect to the object to be edited. When it is judged at the step S1102 that the switch is not pushed down, processing for turning OFF “flag to show it was pushed down last” is executed at step S1109 thereafter to execute processing to return to end position, i.e., flow start position.

When it is judged at the step S1102 that the switch has been pushed down, processing proceeds to step S1103, at which whether or not “flag to show it was pushed down last” is turned ON is judged. In the case where “flag to show it was pushed down last” is not turned “ON”, it is judged that push down of switch of this time is “ON”, i.e., current position is start position of the pull operation. At step S1108, processing for storing position information of pull tool “pinch” of switch-pushing-down-position

into the data memory 103 to return to flow start position is executed.

When it is judged at the step S1103 that "flag to show it was pushed down last" is turned ON, it is judged that the current switch pushing down of this time is "OFF" and this time period is execution period of the pull operation. In this case, at step S1104, position information of the switch pushing position, i.e., position information as end position of the pull operation is stored into the data memory 103.

At the subsequent step S1105, movement quantity of the pull tool "pinch" from the last switch-pushing-down-point to the switch-pushing-down-point of this time is calculated. This movement quantity is effective processing period of the pull operation. At the subsequent step S1106, deformation processing of object is executed on the basis of movement quantity determined at the step S1105. At step S1107, new attribute information obtained by deformation processing, i.e., shape data of object is stored into the data memory. Display of object is carried out on the picture display unit 110 on the basis of new attribute information.

For supplementing the description of the flowchart shown in FIG. 11, explanation will be further given in connection with the case where the pull tool "pinch" is used with reference to the data flow diagram of FIG. 12. In FIG. 12, processing is started by operation of object tool (sensor) 1201 as actor object and pinch tool (sensor) 1202.

From the object tool 1201, orientation information and position information of object are acquired. From the pinch tool 1202, two position information of position



information of the tool and the last position information of tool are acquired. These information correspond to start position and end position of the pull operation by pinch.

On the basis of two position information of tool, calculation processing 1203 of movement quantity of the tool is executed. On the basis of the calculated movement quantity and position information and orientation information of object, calculation processing 1204 of deformation quantity of object is executed.

Further, on the basis of the calculation processing result of this deformation quantity, change processing of attribute information, i.e., deformation processing 1205 is executed. In combination with these processing, rendering processing 1206 as processing for generating display picture with respect to the picture display unit 110 is executed. Thus, rendering processing result is stored into the memory for display, i.e., the frame memory 104 of FIG. 2 and is displayed on the picture display unit 110.

FIG. 13 is a flow for explaining processing in the case where the brush tool as a coloring tool is applied to the object to be edited to apply coloring. Step S1301 is a step for obtaining position/orientation data on the three-dimensional space of "brush" used as a tool. Such data are obtained on the basis of respective sensor outputs in accordance with kind of input unit utilized, i.e., tablets, magnetic sensors and ultrasonic sensors as previously described.

Then, at step S1302, space relationship/relative position between the object to be edited and the editing tool is determined from position/orientation data of the object

to be edited which has been acquired at the previously mentioned step S801 of FIG. 8 and position/orientation data of the editing tool “brush” which has been determined at the step S1301.

Then, at step S1303, judgment as to whether or not deformation processing of the object to be edited using editing tool “brush” is executed is carried out. Such judgment may be such that, e.g., similarly to the previously described pull tool “pinch”, switch is provided at brush to detect push-down of switch, or there may be employed such a configuration to carry out coloring by brush when distance between the object to be edited and the editing tool which is determined at the step S1302 is less than a predetermined distance.

At the subsequent step S1304, coloring processing with respect to the object is executed. The operator sets in advance color in this instance. After coloring processing of the object to be edited is executed at the step S1304, rewritten attribute data of the object to be edited of colored result is stored into the data memory 103 or the external storage unit 106 shown in FIG. 2 at step S1305.

For supplementing explanation of the flowchart shown in FIG. 13, explanation will be further given in connection with processing in the case where coloring tool “brush” is further used with reference to the data flow diagram of FIG. 14. In the data flow of FIG. 14, processing is started by operation of object tool (sensor) 1401 as actor object and brush tool (sensor) 1402.

From the object tool 1401, orientation information and position information of

object are required. From the brush tool 1402, position information of tool is acquired.

Further, from shape information of object which is attribute of the object to be edited which has been acquired in advance, orientation information and position information of the object and position information of tool which are stored in the data memory 103 of FIG. 2, calculation processing 1403 of coloring range is executed. On the basis of this calculation result and surface attribute information of the object, change processing of attribute information, i.e., coloring processing 1404 is executed. In combination with these processing, rendering processing 1405 as processing for generating display picture with respect to the picture display unit 110 is executed, and rendering processing result is stored into memory for display, i.e., the frame memory 104 of FIG. 2 and is displayed on the picture display unit 110.

FIG. 15 is a flow for explaining processing in the case where the spray tool as a coloring tool is applied to the object to be edited to apply coloring. Step S1501 is step for obtaining position/orientation data in the three-dimensional space of "spray" used as coloring tool. As previously described, such data are data obtained on the basis of respective sensor outputs in accordance with kind of input unit utilized, i.e., tablets, magnetic sensors and ultrasonic sensors.

Then, at step S1502, the positional relationship of action range between the object to be edited and the spray is determined from position/orientation data of the object to be edited which has been acquired at the previously mentioned step S801 of FIG. 8 and position/orientation data of editing tool "spray" determined at the step

S1501.

Then, at step S1503, whether or not the positional relationship of action range between the object to be edited and the spray which has been determined at the step S1502 falls within the action area of editing tool "spray" is judged. At the editing tool "spray", area which can be colored by that spray is set in advance. In order that the object to be edited is colored, there results the condition where the positional relationship of action range between the object to be edited and spray falls within the action area of the editing tool "spray". In this case, the action area of the spray is set as attribute of tool in advance.

It is to be noted that, in the spray tool, the action area is set as conical area 1701 in which predetermined points of the spray tool are caused to be vertices as indicated by FIG. 17A, for example, and coloring range 1702 with respect to object is set within the action area on object 1704 surface as shown in FIG. 17B. Push button 1703 is provided at the spray tool, and coloring range 1702 is set on the basis of the positional relationship at the time point when the push button 1703 is pushed down.

When it is judged at the step S1503 that corresponding area is outside the action area of the editing tool "spray", coloring processing by spray is not executed. As a result, processing is completed. Thus, the routine is returned to the start position. When it is judged at the step S1503 that corresponding area is inside the action area of the editing tool "spray", the action area is displayed on the picture display unit 110 at step S1504.

Then, at step S1505, switch of the editing tool “spray” is pushed down, and whether or not the switch is turned ON is judged. With the fact that the switch has been turned ON being as the condition, coloring processing with respect to object is executed at step S1506. The operator sets in advance color in this instance. After coloring processing of the object to be edited is executed at step S1506, rewritten attribute data of the object to be edited of colored result is stored into the data memory 103 or the external storage unit 106 shown in FIG. 2 at step S1507.

For supplementing the description of the flowchart shown in FIG. 15, explanation will be further given in connection with processing in the case where the coloring tool “spray” is used with reference to the data flow diagram of FIG. 16. In the data flow of FIG. 16, processing is started by operation of the object tool (sensor) 1601 as actor object and spray tool (sensor) 1602.

From the object tool 1601, orientation information and position information of the object are acquired. From the spray tool 1602, position information and orientation information of tool are acquired.

On the basis of the position information and the orientation information of the spray tool, calculation processing 1603 of the action area which can be colored by spray is executed.

Further, calculation processing 1604 of the coloring range is carried out on the basis of shape information of the object which is attribute of the object to be edited which has been acquired in advance, orientation information and position information

of object, and calculated action area of spray which are stored in the data memory 103 of FIG. 2, and change processing of attribute information, i.e., coloring processing 1605 is executed on the basis of this calculation. In combination with these processing, rendering processing 1606 as processing for generating display picture with respect to the picture display unit 110 is executed, and rendering processing result is stored into the memory for display, i.e., the frame memory 104 of FIG. 2 and is displayed on the picture display unit 110.

As stated above, in accordance with the three-dimensional model processing apparatus of this invention, the operator uses the object tool corresponding to the object to be edited and various dedicated tools to execute change operation of relative position between both tools, whereby the processing unit executes processing set in advance in accordance with the dedicated tool. As a result, processing corresponding to respective editing tools such as deformation or coloring, etc., i.e., attribute change is carried out with respect to the object to be edited displayed on the picture display unit, and display of its result is executed. Accordingly, operator can execute various processing with such a feeling to directly implement processing to the object to be edited on picture.

Explanation will now be given in connection with the more practical example of application in the three-dimensional model processing apparatus of this invention. The example where the three-dimensional model processing apparatus of this invention is applied to on-line shopping using communication network such as internet, etc. is

shown in FIGS. 18A to 18C.

The three-dimensional model processing apparatus of this invention is constituted within, e.g., personal computers of users to display, on display 1801, goods from provider who provides on-line shopping. Such goods display may be carried out by storing three-dimensional picture data relating to goods provided from provider through network into storage unit such as memory, hard disk, etc. within the computer of the user to read out such data, or may be carried out by using data stored on medium, e.g., CD or DVD, etc. that the goods provider provides.

The user who studies goods displays three-dimensional picture of goods on display 1801 to hold, by one hand, object tool (goods metaphor) 1802 corresponding to the display goods and to hold, by the other hand, operation tool (tool metaphor) 1803 for executing various processing with respect to goods. User who studies goods can relatively operate goods metaphor 1802 and tool metaphor 1803 to execute processing corresponding to respective tool metaphors with respect to goods displayed on display. For example, by changing angle/orientation of goods metaphor 1802, article displayed on display is displayed in the state where angle/orientation is changed in a manner from FIG. 18A to FIG. 18B. Thus, user can observe goods or articles from all angles.

Further, for example, the previously described push tool is used as tool metaphor 1803, and push operation is executed by tool which pushes each operation button portions of goods metaphor corresponding to video camera which is article by the push

tool as shown in FIG. 18C, thereby making it possible to employ such a configuration that operation button portion of video camera on the display 1801 is pushed down so that processing corresponding to push-down operations of each operation button is executed on the display.

This is realized by employing a configuration such that each switch position of the object to be edited is specified on the basis of position information of the push tool to execute processing program corresponding to specified switch. By program execution corresponding to the switch, operation display of goods within display 1801 is carried out. In a manner as stated above, user can actually obtain feeling to practically hand or hold article to operate it by relative operation between goods metaphor and tool metaphor.

Further, explanation will be given in connection with a different more practical example of application in the three-dimensional model processing apparatus of this invention. FIG. 19 constitutes the three-dimensional model processing apparatus of this invention within, e.g., personal computer to display virtual pet on display 1901 of the personal computer to hold, by one hand, object tool 1902 corresponding to the display virtual pet and to hold, by the other hand, various editing tools 1903 to operate the editing tool 1903 with respect to the object tool 1902 corresponding to pet to thereby execute various processing.

For example, there may be employed a configuration such that a microphone tool is caused to be close to object tool 1902 corresponding to pet with the editing tool



1903 being as microphone tool so that displayed pet outputs voice through speaker. This is realized by executing subprogram set in correspondence with the microphone tool in the case where the microphone tool and the object tool 1902 are caused to be close so that distance therebetween is below a predetermined value to execute processing to output voice. Further, setting may be made so as to execute processing to change tone of voice on the basis of orientation information of the object tool at this time.

In addition, various tools such as kennel, feed, etc. are set as the editing tool to set subprograms to carry out execution in correspondence with respective tools so that various processing can be executed in accordance with kind of tools.

As, e.g., processing programs shown in FIGS. 8, 9, 11, 13, 15, etc. in the three-dimensional model processing apparatus of this invention, program stored in the program memory 102 shown in FIG. 2 may be applied, or there may be employed configuration in which program is stored in various memory media such as CD-ROM, CD-R, CD-RW, DVD-RAM, DVD-RW, DVD+RW, MO, hard disk or floppy disk, etc. For example, in the case of the previously goods selling by goods provider, etc., there may be employed a configuration such that processing program is stored in combination on CD where three-dimensional data of goods as goods catalog is stored to offer it to user. In this case, in the case where the user sets CD to display goods on display to execute processing using various editing tools, processing program corresponding to tool is called and is executed. As a result, processing is carried out

in accordance with the tool. Thus, configuration for allowing goods displayed on display to execute various operations is realized.

As stated above, in accordance with the three-dimensional model processing apparatus and the three-dimensional model processing method of this invention, there is employed the configuration in which operator operates various editing tools to execute processing set in accordance with corresponding tool. Accordingly, the operator can execute various processing with a feeling as if he hands or holds the object to be edited displayed on display to directly operate it.

While explanation has been given in connection with this invention with reference to specified embodiments, it is obvious that the person who is skilled in the art can attain modification and/or substitution of the embodiments within the scope which does not depart from the gist. Namely, this invention has been disclosed in the form of exemplification, and should not be restrictively interpreted. In addition, embodiments constituted by combining the above-described embodiments as occasion demands are also included within the scope of this invention. For judging the gist of this invention, the column of the appended patent claims should be taken into consideration.

#### Industrial Applicability

As described above, in accordance with the three-dimensional model processing apparatus and the three-dimensional model processing method according to this

invention, there is employed the configuration that an operator operates various editing tools to execute processing set in accordance with the corresponding tool. Accordingly, the operator can execute various processing with a feeling as if he or she directly operates the object to be edited displayed on the display.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219  
2220  
2221  
2222  
2223  
2224  
2225  
2226  
2227  
2228  
2229  
223